



Description

BCM is a single point type load cell of aluminum material. It is suitable for large sized platform scale, bench scale and counting scale.

Specifications

Capacity(R.L.)	kgf	50, 75, 100, 150, 200, 250, 300, 500, 750	
Rated Output	mV / V	2.0 ± 0.2	
Zero Balance	mV / V	0.0 ± 0.1	
Accuracy Class	-	C3	-
Non-Linearity	% R.O.	≤0.02	≤0.03
Hysteresis	% R.O.	≤0.02	≤0.03
Combined Error	% R.O.	≤0.02	≤0.03
Repeatability	% R.O.	≤0.01	≤0.01
Creep for 30min.	% R.O.	≤0.017	≤0.03
Return for 30min.	% R.O.	≤0.017	≤0.03
Resolution	-	≤1/5000	≤1/3000
Division	mV / V	0.0004	0.00067
Temperature Effect on	-Zero Value	%/10°C	≤0.014
	-Output Value	%/10°C	≤0.011
Excitation	-Recommended	V	10
	-Maximum	V	15
Resistance	-Input	Ω	420 ± 20
	-Output	Ω	350 ± 3.5
	-Insulation	MΩ	> 2000
Compensated Temperature Range	°C	-10 to +40	
Operating Temperature Range	°C	-30 to +80	
Material & Plate	-	Aluminum	
Cable Specification	-	Ø5 x 4P x 3m (Urethane)	
Safety Overload	% R.L.	150	
Platform Size	mm	600 x 600	

Features

- ▶ Pressure type
- ▶ Designed according to IP65

Option

- ▶ OIML C3 approved (OIML R60 (50L~500L))
- ▶ NTEP III 5,000d Approved
- ▶ 6-wire connection

Application

- ▶ Bench Scale
- ▶ Platform Scale

Dimensions

▶ BCM

